

# WEEE TEST REPORT

European Directive 2012/19/EU

Evaluation of WEEE Requirements for Electrical and Electronic Equipment

Test report No..... : NICERD211202.0011

Date of receipt ..... : Dec 02, 2021

Date of issue ..... : Feb 15, 2022

Test of period ..... : Dec 02, 2021 ~ Feb 14, 2022

Applicant's name ..... : Suprema ID Inc.

Address..... : 1207, 37, Sagimakgol-ro 62beon-gil, Jungwon-gu, Seongnam-si, Gyeonggi-do,  
Republic of Korea

Manufacturer's name ..... : Same applicant.

Address..... : Same applicant.

Product name ..... : RealScan S60

Basic Model..... : RS-S60

Multiple Model(s)..... : RealScan S60M, RS-S60M

Test Specifications :

Directive..... : WEEE Directive 2012/19/EU, Article 11 - Recovery targets

Test Standard(s)..... : IEC/TR 62635 : 2012

Test Laboratory..... : NICE Certification Co., Ltd.

Address..... : 3F, 46, Gunpocheomdansaneop 2-ro, Gunpo-si, Gyeonggi-do, Republic of Korea

This publication may be reproduced in whole or in part for non-commercial purpose according to the of applicant. Also it is not allowed to copy this report even partly without the allowance of publisher.

Also this publication represent for the evaluation results of the issued test item only - any type of EEE

The evaluation results means only the tested item is evaluated with recovery requirement of the WEEE Directive according to the evaluation procedures which is described in this publication.

Approved by :



Technical Manager : Kyung-Jun Choi


# INDEX

1.General product information.....	4
2. 2012/19/EU Summary	
2.1 WEEE Directive 2012/19/EU, Article 11 - Recovery targets.....	5
2.2 Disassembly.....	5
2.3 Selective treatment.....	6
3. Recycling and recovery rate of calculation table	
3.1 IEC/TR 62635 Annex D Table D.2.....	7
3.2 IEC/TR 62635 Annex D Table D.3.....	8
3.3 IEC/TR 62635 Annex D Table D.5.....	9
3.4 IEC/TR 62635 Annex D Table D.6.....	10
3.5 IEC/TR 62635 Annex D Table D.7.....	11
4. Evaluation flow	
4.1 Procedure .....	12
4.2 Calculation formula.....	12
5. Disassembling result	
5.1 Component detailed information.....	13
5.2 Calculation.....	18
5.3 Test result.....	18

## 1. General product information



Front view



Rear view

# 1. General product information

Product Category according to Annex III of 2012/19/EU		
Type of Category	: Category 6. Small IT and telecommunications equipment (no external dimension more than 50 cm)	
Total weight (g)	: 258 g	
Connection technique	: ▶ Screw ▶ Bonding, Glue, Adhesive ▶ Soldering ▶ Cable connector	▶ Rotary, Twist ▶ Joints – Molding, Put in etc. ▶ Welding ▶ Others
Disassembly tools	: ▶ Screw driver ▶ Long nose pliers ▶ Hand, Awl	▶ Spanner, wrench ▶ Cutting knife ▶ Cutting pliers ▶ Jig tools (Special)
Disassembly time ( min / sec )	: 55 sec	
Product disassembly assessment	: See 3 Recycling and recovery rate of calculation table	
Recycling rate (%)	: 49.1 %	
Recovery rate (%)	: 54.2 %	

## \* Product Remark

- NICE Certification Co., Ltd. tested the RealScan S60 was selected by applicant.
- The model RS-S60 is the basic model that was tested.
- The applied model RealScan S60M, RS-S60M are identical to the basic model,  
except that the name of model were different.

## 2. 2012/19/EU Summary

### 2.1 WEEE Directive 2012/19/EU , Annex V

Classification	Recycling rate	Recovery rate
<ul style="list-style-type: none"> <li>▶ Temperature exchange equipment</li> <li>▶ Large equipment (any external dimension more than 50 cm) including</li> </ul>	80%	85%
<ul style="list-style-type: none"> <li>▶ Screens, monitors, and equipment containing screens having a surface greater than 100 cm<sup>2</sup></li> </ul>	70%	80%
<ul style="list-style-type: none"> <li>▶ Small equipment (no external dimension more than 50 cm) including</li> <li>▶ Small IT and telecommunication equipment (no external dimension more than 50 cm)</li> </ul>	55%	75%
<ul style="list-style-type: none"> <li>▶ Lamps</li> </ul>	80%	N.A.

### 2.2 Disassembly

The product was disassembled into different parts which were major based on the treatment requirements as a set out in the WEEE Directive Annex VII.

Material, of which a recycling technology is not available or the recycling is not economy and feasible at present, are an assumed to be shredded, incinerated or disposed for landfill without further usage.

## 2. 2012/19/EU Summary

### 2.3 Selective treatment

As a minimum the following substances, preparations and components have to be removed from any separately collected WEEE :

- ▶ Polychlorinated biphenyls (PCBs) containing capacitors in accordance with Council Directive 96/59/EC of 16 September 1996 on the disposal of polychlorinated biphenyls and polychlorinated terphenyls (PCBs/PCTs)
- ▶ Mercury containing component, such as switches or blacklighting lamps
- ▶ Batteries
- ▶ Printed circuit boards of mobile phones generally, and of other devices if the surface of the printed circuit board is greater than 10 square centimeters
- ▶ Toner cartridges, liquid and pasty, as well as colour toner
- ▶ Plastic containing brominated flame retardants
- ▶ Asbestos waste and components which contain asbestos
- ▶ Cathode ray tube
- ▶ Chlorofluorocarbons (CFCs), hydrochlorofluorocarbons (HCFCs) or hydrocarbons (HCs)
- ▶ Gas discharge lamps
- ▶ Liquid crystal displays (together with their casing where appropriate) of a surface greater than 100 square centimetres and all those back-lighted with gas discharge lamps
- ▶ External electric cables
- ▶ Components containing refractory ceramic fibres as described in Commission Directive 97/69/EC of 5 December 1997 adapting to technical progress Council Directive 67/548/EEC relating to the classification, packaging and labeling of dangerous substances
- ▶ Components containing radioactive substances with the exception of component that are below the exemption thresholds set in Article 3 of and Annex I to Council Directive 96/29/Euratom
- ▶ Electrolyte capacitors containing substances of concern ( Height > 25mm, Diameter > 25mm )

### 3. Recycling and recovery rate of calculation table

#### 3.1 IEC/TR 62635 Annex D Table D.2

##### - Recycling and recovery rate of product parts which a single recyclable material

Material name	Recycling rate RCR (%)	Recovery rate RVR (%)
ABS (acrylonitrile butadiene styrene)	90	90
PP (polypropylene)	90	90
HIPS (high impact polystyrene)	90	90
GPPS (general purpose polystyrene)	98	98
SAN (styrene acrylonitrile)	98	98
PC (polycarbonate)	90	90
Steel (general)	95	95
Stainless steel (magnetic)	95	95
Stainless steel (non-magnetic)	95	95
Aluminum	95	95
Copper	98	98
Nickel pure	95	95
Zinc die casting	95	95
Magnesium	95	95
PMMA (polymethyl methacrylate)*	70	90
EP (EPOXY resin)	0	90
PF (phenol formaldehyde resin)	0	90
PUR (polyurethane foam)	0	90
Glass (door panel)	0	0
Glass (shelf)	0	0

► Note

\* ; Applied IEC/TR Annex D Table D.4 of PMMA

### 3. Recycling and recovery rate of calculation table

#### 3.2 IEC/TR 62635 Annex D Table D.3

##### - Recycling and recovery rate of product parts difficult to process

Part name	Recycling rate RCR (%)	Recovery rate RVR (%)
Compressors	90	90
AC motor	90	90
Resin motor	0	0
Clutch	90	90
Evaporator	90	90
Transformer (MWO : microwave oven transformer)	90	90
Cement weight balance	0	0
Steel weight balance	90	90



### 3. Recycling and recovery rate of calculation table

#### 3.3 IEC/TR 62635 Annex D Table D.5

##### - Recycling and recovery rate of product parts which require selective treatment

Part or material	Recycling rate RCR (%)	Recovery rate RVR (%)
Cable (high current)	33	33
Cable (low current)	24	24
Battery (lead-acid)	60	60
Battery (Ni-Cd) (2 type : portable (<1 kg), non-portable (>1kg))	70	70
Other battery	45	45
PWB (Printed wiring board with components) - Poor	14	57
PWB (Printed wiring board with components) - Intermediate	17	60
PWB (Printed wiring board with components) - Rich	18	61
CRT (cathode-ray tube)	90	90
LCD (liquid crystal display)*	0	0

#### ► Note

\*; Applied IEC/TR Annex D Table D.1 of LCD

### 3. Recycling and recovery rate of calculation table

#### 3.4 IEC/TR 62635 Annex D Table D.6

##### - Recycling and recovery rate of product parts which a single recyclable material

Material name	Recycling rate RCR (%)	Recovery rate RVR (%)
ABS (acrylonitrile butadiene styrene)	94	95
ABS with any additives	94	95
PP (polypropylene)	94	95
PP + EPDM	94	95
PP - GF (polypropylene + glass fibre)	94	95
PP with natural fibres (e.g. hemp)	0	97
PP with any other additives	94	95
HIPS (high impact polystyrene)	94	95
HIPS with any additives	94	95
PE (polypropylene copolymer)	94	95
SAN (styrene acrylonitrile) with and without additives	94	95
ABS-PC with and without additives	94	95
PA (polyamide) with and without additives	94	95
PA-6 with and without additives	94	95
PMMA (polymethyl methacrylate)*	70	90
PET (polyethylene terephthalate)*	70	90
Other polymers	0	5
Steel (general)	95	95
Aluminum	95	95
Copper	95	95
Other metal	95	95

► Note

\* ; Applied IEC/TR Annex D Table D.4 of PMMA and PET

### 3. Recycling and recovery rate of calculation table

#### 3.5 IEC/TR 62635 Annex D Table D.7

##### - Recycling and recovery rate of product parts difficult to process


Part name	Recycling rate RCR (%)	Recovery rate RVR (%)
AC motor	85	85
Heatsink	93	93
Cable (optical)	0	0
Bulb	0	0
Cable*	33	33

► Note

\* ; Applied IEC/TR Annex D Table D.5 of cable (high current)

## 4. Evaluation flow

### 4.1 Procedure



### 4.2 Calculation formula

Recycling Rate (%)	=	$\frac{\text{Recycling total weight}}{\text{Product total weight}} \times 100\%$
Recovery Rate (%)	=	$\frac{\text{Recovery total weight}}{\text{Product total weight}} \times 100\%$





## 5. Disassembling results

### 5.1 Component detailed information

1		Part name ;		Main product	Connection type	-
		Material type ;		Composite	Evaluation	Further disassembly
		Disassembly tools		-	Disassembly time(sec)	-
		Weight (g)	Recycling rate(%)	Recycling weight (g)	Recovery rate(%)	Recovery weight (g)
		-	N.A.	-	N.A.	-
2		Part name ;		Rubber Foot	Connection type	Tape
		Material type ;		Other polymers	Evaluation	Table D.6
		Disassembly tools		Hand	Disassembly time(sec)	4
		Weight (g)	Recycling rate(%)	Recycling weight (g)	Recovery rate(%)	Recovery weight (g)
		1.20	0	0.00	5	0.06
3		Part name ;		Tape Sealing Screw	Connection type	Tape
		Material type ;		Other polymers	Evaluation	Table D.6
		Disassembly tools		Knife	Disassembly time(sec)	4
		Weight (g)	Recycling rate(%)	Recycling weight (g)	Recovery rate(%)	Recovery weight (g)
		0.04	0	0.00	5	0.00
4		Part name ;		Rear case	Connection type	Screw(4)
		Material type ;		PC	Evaluation	Table D.6
		Disassembly tools		Screw driver	Disassembly time(sec)	8
		Weight (g)	Recycling rate(%)	Recycling weight (g)	Recovery rate(%)	Recovery weight (g)
		41.3	94	38.8	95	39.2





## 5. Disassembling results

### 5.1 Component detailed information

5		Part name ;		Rubber O-ring	Connection type	Putting
		Material type ;		Other polymers	Evaluation	Table D.6
		Disassembly tools		Hand	Disassembly time(sec)	1
		Weight (g)	Recycling rate(%)	Recycling weight (g)	Recovery rate(%)	Recovery weight (g)
		0.42	0	0.00	5	0.02
6		Part name ;		UI_BOARD	Connection type	Screw(2)
		Material type ;		PWB	Evaluation	Table D.5
		Disassembly tools		Screw driver	Disassembly time(sec)	4
		Weight (g)	Recycling rate(%)	Recycling weight (g)	Recovery rate(%)	Recovery weight (g)
		5.38	18	0.97	61	3.28
7		Part name ;		Module Frame Bottom	Connection type	Residue
		Material type ;		SUS304	Evaluation	Table D.6
		Disassembly tools		-	Disassembly time(sec)	-
		Weight (g)	Recycling rate(%)	Recycling weight (g)	Recovery rate(%)	Recovery weight (g)
		29.7	95	28.2	95	28.2
8		Part name ;		Label	Connection type	Tape
		Material type ;		PP Film HPALM90	Evaluation	Disposal
		Disassembly tools		Knife	Disassembly time(sec)	1
		Weight (g)	Recycling rate(%)	Recycling weight (g)	Recovery rate(%)	Recovery weight (g)
		0.05	0	0.00	0	0.00





## 5. Disassembling results

### 5.1 Component detailed information

9		Part name ;		Module PCB	Connection type	Screw(4)
		Material type ;		PWB	Evaluation	Table D.5
		Disassembly tools		Screw driver	Disassembly time(sec)	8
		Weight (g)	Recycling rate(%)	Recycling weight (g)	Recovery rate(%)	Recovery weight (g)
		23.4	18	4.21	61	14.3
10		Part name ;		LCD	Connection type	Tape
		Material type ;		Composite	Evaluation	Table D.5
		Disassembly tools		Cutting plier	Disassembly time(sec)	4
		Weight (g)	Recycling rate(%)	Recycling weight (g)	Recovery rate(%)	Recovery weight (g)
		73.8	0	0.00	0	0.00
11		Part name ;		Indicator	Connection type	Tape
		Material type ;		PC	Evaluation	Table D.6
		Disassembly tools		Cutting plier	Disassembly time(sec)	5
		Weight (g)	Recycling rate(%)	Recycling weight (g)	Recovery rate(%)	Recovery weight (g)
		0.54	94	0.51	95	0.51
12		Part name ;		Front case	Connection type	Residue
		Material type ;		PC	Evaluation	Table D.6
		Disassembly tools		-	Disassembly time(sec)	-
		Weight (g)	Recycling rate(%)	Recycling weight (g)	Recovery rate(%)	Recovery weight (g)
		36.4	94	34.2	95	34.6

## 5. Disassembling results




### 5.1 Component detailed information

13		Part name ;		Insert	Connection type	Molding
		Material type ;		Copper	Evaluation	Table D.6
		Disassembly tools		Cutting plier	Disassembly time(sec)	16
		Weight (g)	Recycling rate(%)	Recycling weight (g)	Recovery rate(%)	Recovery weight (g)
		6.25	95	5.94	95	5.94
14		Part name ;		Tape	Connection type	Residue
		Material type ;		Composite	Evaluation	Disposal
		Disassembly tools		-	Disassembly time(sec)	-
		Weight (g)	Recycling rate(%)	Recycling weight (g)	Recovery rate(%)	Recovery weight (g)
		0.23	0	0.00	0	0.00
15		Part name ;		Screw	Connection type	Residue
		Material type ;		Other metal	Evaluation	Table D.6
		Disassembly tools		-	Disassembly time(sec)	-
		Weight (g)	Recycling rate(%)	Recycling weight (g)	Recovery rate(%)	Recovery weight (g)
		0.54	95	0.51	95	0.51
16		Part name ;		Screw	Connection type	Residue
		Material type ;		Other metal	Evaluation	Table D.6
		Disassembly tools		-	Disassembly time(sec)	-
		Weight (g)	Recycling rate(%)	Recycling weight (g)	Recovery rate(%)	Recovery weight (g)
		0.31	95	0.29	95	0.29



## 5. Disassembling results

### 5.1 Component detailed information

17		Part name ;		Screw	Connection type	Residue
		Material type ;		Other metal	Evaluation	Table D.6
		Disassembly tools		-	Disassembly time(sec)	-
		Weight (g)	Recycling rate(%)	Recycling weight (g)	Recovery rate(%)	Recovery weight (g)
		0.63	95	0.60	95	0.60
18		Part name ;		Cable Tie	Connection type	Tie
		Material type ;		Composite	Evaluation	Disposal
		Disassembly tools		-	Disassembly time(sec)	-
		Weight (g)	Recycling rate(%)	Recycling weight (g)	Recovery rate(%)	Recovery weight (g)
		0.42	0	0.00	0	0.00
19		Part name ;		USB Cable	Connection type	Residue
		Material type ;		Cable Tie	Evaluation	Table D.5
		Disassembly tools		-	Disassembly time(sec)	-
		Weight (g)	Recycling rate(%)	Recycling weight (g)	Recovery rate(%)	Recovery weight (g)
		37.7	33	12.4	33	12.4

~~ The complete disassembly ~~

## 5. Disassembling results

### 5.2 Calculation

Information	Weight (g)	Weight (%)
1. Product total	258	100
2. Recycling	127	49.1
3. Recovery	140	54.2
4. Disposal	0.70	0.27

Other information	Calculation formula
Recycling Rate (%)	$= \frac{\text{Recycling total weight}}{\text{Product total weight}} \times 100\%$
Recovery Rate (%)	$= \frac{\text{Recovery total weight}}{\text{Product total weight}} \times 100\%$

### 5.3 Test result

Item	Target	Test result
Recycling Rate (%)	55%	49.1%
Recovery Rate (%)	75%	54.2%