

xperix

BioMini Slim 2

Ultra-slim FAP20 Authentication Scanner



BioMini Slim 2 is FAP20 certified fingerprint scanner featuring an array of cutting-edge technologies. Along with its 13.5mm slim optical sensor, BioMini Slim 2 features Xperix's proprietary Multi-dynamic Range (M-DR) technology, FBI PIV and Mobile ID FAP20 compliance and Android device support. BioMini Slim 2 also provides developers more physical flexibility with its reduced form factor and the ultra-slim optical sensor ensures robust operation over time. BioMini Slim 2 provides advanced artificial Intelligence-based Live Finger Detection technology which is compliant with ISO 30107-3 PAD Level 1 & 2 Standard. Applying LFD technology, BioMini Slim 2 distinguishes fake fingerprints made from various materials including clay, rubber, silicon, glue, paper, film, and more.



BioMini Slim 2

Ultra-slim FAP20 Authentication Scanner

FEATURES



· World's slimmest FAP 20 optical sensor



· FBI PIV and FBI Mobile ID FAP20 certificates
· Image compression standard: WSQ



· Capturing high-quality fingerprint images even when the finger is dry & wet.
· Operates under direct sunlight up to 100,000 LUX



· Live Fingerprint Detection (LFD) Technology
- ISO 30107-3 Compliant (PAD Level 1 & 2)
- Distinguishes fake fingerprints made from various materials including clay, rubber, silicon, glue, paper, film and more



· Easy Integration
- BioMini SDK for easy application development
- Android, MS Windows & Linux compatible
- Multi-threaded code design for multi-core CPU utilization



· No need to type in a password
· Instant login by touching your finger

SPECIFICATIONS

| | | |
|---------------|---------------------------------|--|
| Sensor | Image Quality Standards | FBI PIV / FBI Mobile ID FAP20 |
| | Live Finger Detection | O |
| | Sensor Type | Optical |
| | Resolution | 500 ppi |
| | Image Grayscale | 8 bit, 256 levels |
| | Platen Size (W x L mm) | 16.5 x 21.0 |
| | Sensing Area (W x H mm) | 15.24 x 20.32 |
| H/W | Image Size (W x H pixels) | 300 x 400 |
| | Interface | USB 2.0 High Speed |
| | Sensor Surface | Optic Glass, Scratch-free |
| | Operating Temperature(°C) | -10~50°C |
| | Operating humidity | 0 ~ 90% RH |
| | Ingress Protection | IP65 (Sensor Surface) |
| | Dimensions (W x L x H mm) | 72.8 X 40.7 X 18.5 |
| S/W | Weight | 91g |
| | Windows | Windows 7 or later 32/64bit |
| | Linux | Ubuntu, Debian, Fedora, OpenSUSE, Cent OS 32/64bit |
| | Android Android 5.0 or later | O |
| | Image Format | RAW, BMP, WSQ, ISO 19794-4 |
| | Template Type | Xperix, ISO 19794-2, ANSI-378 |
| | Live Finger Detection | ISO 30107-3 Complaint (PAD Level 1 & 2) |
| Certification | CE | O |
| | FCC | O |
| | RoHS | O |
| | UL | X |
| | USB-IF | X |
| | CB | O |
| | IEC62471 | O |
| | WEEE | O |
| | REACH | O |
| | WHQL | O |



Xperix Inc.

#305~308, 3F, Building A, Tera Tower 2, 201 Songpa-daero, Songpa-gu, Seoul, Republic of Korea
T +82 1588 8817 E sales_id@xperix.com www.xperix.com

©2024 Xperix Inc. Xperix and identifying product names and numbers herein are registered trade marks of Xperix Inc. All non-Xperix brands and product names are trademarks or registered trademarks of their respective companies. Product appearance, build status and/or specifications are subject to change without notice.